

Basic

easy-to-use and reliable swimming pool heat pump

Silent efficiencyR reversible__ intuitive





easy-to-use andreliable swimming pool heat pump

Basic

	Basic 4	Basic 6	Basic 8	Basic 10
Swimming pool volume (mai-september, with cover)	20-30 m³	30-40 m³	40-50 m³	50-60 m³
Air 26C / Water 26°C / Hygro 80%				
Heating capacity	3,80 kW	5,80 kW	8,70 kW	11,00 kW
Power consumed	0,83 kW	1,26 kW	1,74 kW	2,16 kW
COP	4,60	4,60	5,00	5,10
Air 15°C / Water 26°C / Hygro 70%*				
Heating capacity	2,90 kW	4,80 kW	6,50 kW	8,80 kW
Power consumed	0,69 kW	1,12 kW	1,51 kW	2,05 kW
COP	4,20	4,30	4,30	4,30
Minimal water flow	3 m³/h	3 m³/h	4 m³/h	5 m³/h
Noise level (at 10 meters)	33 dB(a)	33 dB(a)	34 dB(a)	35 dB(a)
Net weight	36 kg	43 kg	50 kg	70 kg
Refrigerant	R32	R32	R32	R32

^{*}Tested at 15°C ambient air and water inlet 26°C outlet 28°C with 70% humidity following recommendation of the FPP and European norms.

COP Coefficient Of Performance = Heating capacity/Power consumption

- Intuitive LED display
 3 operating modes:
 Heating, Cooling, Automatic
- Automatic defrost by cycle inversion
 4 way valve: quick and efficient defrost
- Remotable display
 Install your display into the pool-housse
 Up to 10 meters (optionnal cable)
- « Blue fins » Evaporator and riffled copper tubes
 Better corrosion resistance and condensate water evacuation, optimal performance
- Rotative compressor
 Reliable, efficient and quiet

- Titanium condenser in PVC shell
 Efficiency and high corrosion resistance
- Certification CE
 Heating capacity and COP certified by our certified laboratory
- Anti-UV ABS casing
 Weather and UV resistant
- 2-year warranty
 Heat pump guaranteed for 2 years
- Accessories included:
- Anti-vibrating supports Silentblocs
- Hydraulic connectiors
- Condensate drainage pipe





