

| Product information sheet | | | |
|--|-------|--|-------|
| Lighting technology used | LED | Non-directional or directional | NDLS |
| Mains or non-mains | NMLS | Connected light source (CLS) | no |
| Colour-tuneable light source | no | Envelope | no |
| High luminance light source | no | | |
| Anti-glare shield | no | Dimmable | YES |
| Product parameters | | | |
| Parameter | Value | Parameter | Value |
| General product parameters | | | |
| Energy consumption in on-mode (kWh/ 1 000 h | 4 | Energy efficiency class | G |
| Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 270lm | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2700K |
| On-mode power (P_{on}), expressed in W | 4W | Standby power (P_{sb}), expressed in W and rounded to the second decimal | 0W |
| Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | | Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set | |

| | | | |
|---|---------|---|------|
| Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre) | Height: | Spectral power distribution in the range 250 nm to 800 nm, at full-load | |
| | Width: | | |
| | Depth: | | |
| Claim of equivalent power | yes | If yes, equivalent power (W) | 35 |
| Parameters for directional light sources | | | |
| Peak luminous intensity (cd) | | Beam angle in degrees, or the range of beam angles that can be set | |
| Parameters for LED and OLED light sources | | | |
| R9 colour rendering index value | >80 | Survival factor | 0.85 |
| the lumen maintenance factor | >0.96 | | |
| Parameters for LED and OLED mains light sources | | | |
| displacement factor ($\cos \phi_1$) | | Colour consistency in McAdam ellipses McAdam | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | If yes then replacement claim (W) | |
| Flicker metric (Pst LM) | | Stroboscopic effect metric (SVM) | |