## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	PELEGATED REGUI	-AHON (EU) 2019/2	015 with regard to energ	gy labelling of light
Supplier's name	e or trade mark:	Shelly		
Supplier's addre	ess: Allterco, Che	rni Vrh Boulevard 1	03 103, 1407 Sofia, BG	
Model identifie	er: 38002352622	90		
Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)		GU10		
Mains or non-m	nains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable	e light source:	Yes	Envelope:	-
High luminance	light source:	Yes		
Anti-glare shield	d:	Yes	Dimmable:	Yes
		Product para		
Parameter		Value	Parameter	Value
		General product p		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode power (P <sub>on</sub> ), expressed in W		5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,99	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	70	Spectral power	See image
dimensions	Width	50	distribution in the	in last page
without	Depth	50		Page 1 /

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40			
		Chromaticity	0,313			
		coordinates (x and y)	0,337			
Parameters for directional light sources:						
Peak luminous intensity (cd)	-	Beam angle in degrees, or the range of beam angles that can be set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	24	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	0			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,9	Stroboscopic effect metric (SVM)	0,3			

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;